





Model	14/115	10/125	7/170
<b>COMPRESSOR</b>			
Free Air Delivery - m <sup>3</sup> /min (cfm)	11.3 (400)	12.7 (450)	17 (600)
Rated Operating Pressure - bar (psi)	14 (200)	10.3 (150)	7 (100)
<b>INTERNAL SETTINGS</b>			
Maximum allowable pressure - bar (psi)	15.5 (225)	12.1 (175)	8.6 (125)
Safety valve setting - bar (psi)	17.2 (250)	13.8 (200)	12 (175)
<b>ENGINE</b>			
Make	John Deere	John Deere	John Deere
Model	6IRF8AE	6IRF8AE	6IRF8AE
No. of cylinders	6	6	6
Full load speed - rpm	2200	2200	2200
Power - kW (HP)	129 (173)	129 (173)	129 (173)
Electrical - volts	24	24	24
Cooling	Water	Water	Water
Fuel tank capacity - litres	276	276	276
Air outlets BSPT (British Standard Pipe Thread)	1x2", 1x1¼", 2x¾"	1x2", 1x1¼", 2x¾"	1x2", 1x1¼", 2x¾"
Emissions Tier Level	Stage IIIA	Stage IIIA	Stage IIIA
<b>SOUND LEVEL DATA</b>			
Fully compliant to outdoor noise directive 2000/14/EC (2006) - L <sub>WA</sub>	99	99	99
<b>TYRES</b>			
Tyre size	205/75 R17.5	205/75 R17.5	205/75 R17.5 **
Number of wheels	2	2	2
<b>DIMENSIONS (WITH RUNNING GEAR)</b>			
Length (fixed height) - mm	4852	4852	4852
Length min/max (adjustable height) - mm	4793 / 4998	4793 / 4998	4793 / 4998
Width - mm	1985	1985	1985
Height - mm	1890	1890	1890
Ground clearance - mm	250	250	250
Weight (net) fixed/adjustable - kg	2570 / 2650	2570 / 2650	2570 / 2650
Weight (working) fixed/adjustable - kg	2770 / 2850	2770 / 2850	2770 / 2850
<b>DIMENSIONS (ON SHIPPING SUPPORT)</b>			
Length - mm	3122	3122	3122
Width - mm	1550	1550	1550
Height - mm	2055	2055	2055
Weight (net) - kg	2420	2420	2420
Weight (working) - kg	2745	2745	2745



[www.doosanportablepower.eu](http://www.doosanportablepower.eu)



**Portable Power**